



# Turret mill Model EMI5000VS

FOB Lévis\*

## CAPACITIES :

**Spindle :**  
**Taper :** ISO 40  
**Travel X :** 47"  
**Travel X :** 15"  
**Travel Z :** 20"

## CHARACTERISTICS

- Automatic lubricator
- «Turcite B» on «x & z»
- Power feed gear box for x-axis
- Square saddle «box-type» in «x & z»
- Reduction gearbox harder steel machine
- Saddle & table hardened & ground
- Main machine body made of meehanite casting

## INCLUDES

- Air drawball
- Working light
- Drill chuck 5/8"
- Coolant system
- Spring collets set
- Table elevating motor
- Precision milling swivel vice
- Box type ways «x & «z»
- 3-axis Mitutoyo KA digital readout

<b>Spindle feeds :</b>	0.0016", 0.0032", 0.0051"/ revolution
<b>Speed of the spindle :</b>	50 - 4000 rpm (Inverter AC)
<b>Travels :</b>	47" x 15" x 19" (with power feed 2 HP)
<b>Table :</b>	12" x 60"
<b>Distance spindle - column :</b>	0" – 21"
<b>Table capacity :</b>	680 lbs
<b>Stroke :</b>	6"
<b>Motor :</b>	5 HP, 575V, 3ph, 60hz
<b>Dimensions :</b>	82" x 81" x 95" h
<b>Approximate weight :</b>	4 ,950 lbs

\*Specifications and price are subject to changes without prior notice.

\*Machines may differ from photo.



50 rue Delisle  
Lévis, Québec G6V 6K2  
Tél : (418) 837-5832  
Télé : (418) 837-6628  
Courriel : info@garantmachinerie.com

