

Turret mill Model EMIS4A



FOB Lévis*

CAPACITIES :

Spindle:
Taper : ISO 40
Travel X : 34"
Travel Y : 16"
Travel Z : 18"

CHARACTERISTICS

- Automatic lubricator
- "Turcite B" on «X» & «Y»
- Power feed gear box for X-axis
- Square saddle "box-type" in «X» & «Y»
- Saddle and table are hardened & ground
- Reduction gearbox harder than steel machine
- Infinitely variables speed (inversion "inverter drive")
- Main machine body is made from «Meehanite» casting

INCLUDES

- Working light
- Drill chuck 5/8"
- Air drawbar
- Coolant system
- Spring collet set
- Table elevating motor
- Box type ways «X» & «Z»
- Precision milling swivel vice
- 3-axis Mitutoyo KA digital readout

Spindle stroke :	5"
Table :	10" x 54"
Spindle speeds :	60 to 4000 rpm (Inverter AC)
Spindle feeds :	0.0016", 0.0032", 0.0059" / revolution
Table capacity :	660 lbs
Distance spindle - column :	2.75" – 20 1/2"
Motor :	5 HP, 575V, 3ph, 60hz
Dimensions:	67" x 63" x 75" h
Approximate weight :	3 ,300 lbs

*Specifications and price are subject to changes without prior notice.

*Machines may differ from photo.



50 rue Delisle
Lévis, Québec G6V 6K2
Tél : (418) 837-5832
Télééc : (418) 837-6628
Courriel : info@garantmachinerie.com

