

Hydraulic Press Brake Élite RUPB Serie



RUPB175-13

RUPB Specifications

Model	Capacity (tons)	Bed Length	Between Housing	Throat Depth	Stroke	Maximum Opening	Approach Speed	Bending Speed	Return Speed	Backgauge Travel	Motor (HP)	Dimensions (L X P X H)	Approx. Weight
RUPB44-6	44	78"	63"	7 7/8"	4"	13"	4"/s	0.42"/sec	2.36"/sec	19.5"	5.4	91 X 45 X 80	6,600 lbs
RUPB70-6	70	78"	61"	9 7/8"	4"	13"	4"/s	0.32"/sec	1.58"/sec	19.5"	7.5	91 X 54 X 87	8,000 lbs
RUPB70-8	70	98"	79.5"	9 7/8"	4"	13"	4"/s	0.32"/sec	1.58"/sec	19.5"	7.5	110 X 54 X 87	8,820 lbs
RUPB70-10	70	126"	101"	9 7/8"	4"	13"	4"/s	0.32"/sec	1.58"/sec	19.5"	7.5	138 X 54 X 98	10,500 lbs
RUPB88-8	88	98"	79"	9 7/8"	4"	13"	4"/s	0.32"/sec	2.36"/sec	19.5"	7.5	110 X 55 X 91	10,150 lbs
RUPB88-10	88	126"	100"	9 7/8"	4"	13"	4"/s	0.32"/sec	2.36"/sec	19.5"	7.5	138 X 55 X 93	12,100 lbs
RUPB110-10	110	126"	100"	12 1/2"	5 1/8"	15"	4"/s	0.32"/sec	2.6"/sec	19.5"	10	138 X 62 X 98	14,000 lbs
RUPB110-13	110	157"	122"	12 1/2"	5 1/8"	15"	4"/s	0.32"/sec	2.6"/sec	19.5"	10	169 X 62 X 107	18,100 lbs
RUPB135-10	135	126"	100"	12 1/2"	5 1/8"	15"	3.2"/s	0.33"/sec	2.9"/sec	19.5"	10	138 X 63 X 102	16,160 lbs
RUPB135-13	135	157"	122"	12 1/2"	5 1/8"	15"	3.2"/s	0.33"/sec	2.9"/sec	19.5"	10	169 X 63 X 111	19,200 lbs
RUPB175-10	175	126"	100"	12 1/2"	5 7/8"	15.7"	3.2"/s	0.28"/sec	2.68"/sec	19.5"	15	138 X 65 X 106	19,200 lbs
RUPB175-13	175	157"	122"	12 1/2"	5 7/8"	15.7"	3.2"/s	0.28"/sec	2.68"/sec	19.5"	15	169 X 65 X 106	25,200 lbs
RUPB220-10	220	126"	100"	12 1/2"	7 7/8"	17"	3.2"/s	0.28"/sec	2.36"/sec	19.5"	20	138 X 67 X 110	23,200 lbs
RUPB220-13	220	157"	122"	12 1/2"	7 7/8"	18"	3.2"/s	0.28"/sec	2.36"/sec	19.5"	20	169 X 67 X 118	29,500 lbs
RUPB330-10	350	126"	96"	15 3/4"	9 7/8"	19.7"	3.2"/s	0.25"/sec	2.5"/sec	27.5"	30	141 X 87 X 129	41,800 lbs
RUPB330-13	350	157"	126"	15 3/4"	9 7/8"	19.7"	3.2"/s	0.25"/sec	2.5"/sec	27.5"	30	193 X 87 X 142	48,400 lbs

P.S. Other models are available on demand

* Specifications are subject to change without prior notice



The Élite RUPB serie of hydraulic press brakes is offered with multiple advantages, namely:

- Support arms
- Adjustable holding time
- Adjustable speed change point (for bending)
- Side & rear interlocked safety guarding with interruptors
- Constructed with heavy duty steel to assure a minimum of deflections
- European type sectionalized tooling, gooseneck type & multiple-opening 4-way die
- Heavy duty power backgauge (22", 20 (std) / 40 (CNC) / mm/sec) with backgauge finger
- LED digital display for power backgauge & power depth control
- Pedestal console with two hand control & emergency stop
- Reliability selected hydraulic & electrical components
(NOK joints, SCHNEIDER interruptors, SIEMENS relays & contactors, CML pump, YUKEN & JEOUGANG valves, SIKO digital reader)
- Sectional die clamping bars
- Hydraulic overload protection

Optional (RUPB serie):

- NC (Italian) and CNC (DELEM, CYBELEC) Controllers
- FIESSLER laser protection (Germany)
- Manual crowning compensation system
- Quick action clamping device
- Additional backgauge fingers
- Non standard features (ton, lenght, stroke, backgauge depth, throat, speeds, composants, etc.)