



# Geared head, engine lathe Model DML1660-3

FOB Lévis\*

## CAPACITIES :

**Over ways :** 16"  
**Over cross slide :** 9"  
**Between centers :** 60"  
**In gap :** 27"

## CHARACTERISTICS

- Mechanical clutch
- Simplified threading dial
- Clutch located on carriage
- Longitudinal & cross feeds
- Hardened & ground spindles
- Imperial & metric threading
- Hardened & ground bedways
- High density cast iron base

## INCLUDES

- Live center
- Steady rest
- Follow rest
- Live center
- Halogen lamp
- Quick toolpost
- Face plate (12")
- Removable gap
- Coolant system
- Tools & manual
- Production stop
- 3-jaw chuck (6")
- 4-jaw chuck (8")
- Thread chasing dial
- Spindle taper sleeve
- Full length splash guard
- Taper turning attachment
- 2-axis digital readout system

<b>Spindle bore :</b>	3 1/8"
<b>Attachment :</b>	D1 - 8
<b>Speed of the spindle :</b>	26 to 2000 rpm (16)
<b>Feeds :</b>	0.0017" – 0.0583" / revolution (20, longitudinal) 0.0009" – 0.029" / revolution (20, transversal)
<b>Threads :</b>	Imperial : 7/16 to 80 tpi (40) Metric : 0.35 to 80 mm (67)
<b>Tailstock taper :</b>	MT #5
<b>Bed width :</b>	15 1/2"
<b>Tailstock travel :</b>	5.750"
<b>Motor :</b>	10 HP, 575V, 3ph, 60hz
<b>Dimensions :</b>	100" x 40" x 65" h
<b>Approximate weight :</b>	6, 490 lbs

\*Specifications and price are subject to changes without prior notice.

\*Machines may differ from photo.



50 rue Delisle  
Lévis, Québec G6V 6K2  
Tél : (418) 837-5832  
Télec : (418) 837-6628  
Courriel : [info@garantmachinerie.com](mailto:info@garantmachinerie.com)

