



Geared Head Engine Lathe Model DML 25120-5

FOB Lévis*

CAPACITY :

Over ways : 25"
Over cross slide : 13 1/2"
Between centers : 120"
In Gap : 31 1/12"

CHARACTERISTICS

- Mechanical type clutch
- Simplified threading dial
- Longitudinal & cross feeds
- Imperial & metric threading
- High density cast iron base
- Hardened & ground spindles
- Hardened & ground bedways

INCLUDES

- Live center
- Driver plate
- Tools & manual
- Coolant system
- Face plate (12")
- 3-jaw chuck (6")
- 4-jaw chuck (8")
- Removable gap
- Follow & Steady rest
- Halogen lamp (110V)
- Spindle taper sleeve
- Quick change tool post
- Full length splash guard
- Taper turning attachment
- Larger steady & follow rest
- 2-axis digital readout system

Spindle bore :	5 1/16"
Attachment :	D1 - 8
Speed of the spindle :	7.5 à 1000 rpm (16)
Feeds :	0.0039" – 0.96" / revolution (20, longitudinale) 0.002" – 0.48" / revolution (20, transversale)
Threads :	Imperial : 14 – 1 tpi (26) Metric : 1 to 240 mm (39)
Tailstock taper :	MT #6
Bed width :	21.5"
Tailstock travel :	9.250"
Motor :	20 HP, 575V, 3 ph, 60 hz
Overall dimensions :	205" x 40" x 72" h
Approximate weight :	10 ,300 lbs

*Specifications & price are subject to changes without prior notice.

*Machines may differ from photo.



50 rue Delisle
Lévis, Québec G6V 6K2
Tél : (418) 837-5832
Télé : (418) 837-6628
Courriel : info@garantmachinerie.com

