



# Geared head, engine lathe Model WSL1334

| FOB Lévis\*

## CAPACITIES :

**Over ways :** 13"  
**Over cross slide :** 17 ½"  
**Between centers :** 34"  
**In gap :** 7 ¾"

## CHARACTERISTICS

- Clutch located on carriage
- Longitudinal & cross feeds
- Hardened & ground spindles
- Imperial & metric threading
- Hardened & ground bedways
- Simplified quick change levers
- Hardened & ground transmission shafts

## INCLUDES

- Live center
- Follow rest
- Steady rest
- Chuck guard
- Halogen lamp (110V)
- Quick toolpost
- Face plate (10")
- Removable gap
- Coolant system
- Tools & manual
- 3-jaw chuck (8")
- 4-jaw chuck (8")
- Thread chasing dial
- Spindle taper sleeve
- Full length splash guard
- 4-way tool post (1" cap)

<b>Spindle bore :</b>	1.500"
<b>Attachment :</b>	D1 - 4
<b>Speed of the spindle :</b>	70 to 2000 rpm (8)
<b>Feeds :</b>	0.003" – 0.051" / revolution (20, longitudinal) 0.001" – 0.011" / revolution (20, longitudinal)
<b>Threads :</b>	Imperial : 4 to 60 tpi Metric : 0.45 to 7 mm (20)
<b>Tailstock taper :</b>	MT #3
<b>Bed width :</b>	6"
<b>Tailstock travel :</b>	3 ⅞"
<b>Motor :</b>	1.5 HP, 220V, 1ph, 60
<b>Dimensions :</b>	62" x 27" x 50" h
<b>Approximate weight :</b>	1,250 lbs

\*Specifications and price are subject to changes without prior notice.

\*Machines may differ from photo.



50 rue Delisle  
Lévis, Québec G6V 6K2  
Tél : (418) 837-5832  
Télé : (418) 837-6628  
Courriel : [info@garantmachinerie.com](mailto:info@garantmachinerie.com)

