



# Geared head, engine lathe Model WSL1440B

| FOB Lévis\*

## CAPACITIES :

**Over ways :** 14"  
**Over cross slide :** 8.250"  
**Between centers :** 40"  
**In gap :** 20"

## CHARACTERISTICS

- Clutch located on carriage
- Longitudinal & cross feeds
- Hardened & ground spindles
- Imperial & metric threading
- Hardened & ground bedways
- Simplified quick change levers

## INCLUDES

- Live center
- Follow rest
- Halogen lamp
- Quick toolpost
- Face plate (12")
- Removable gap
- Coolant system
- Tools & manual
- Production stop
- 3-jaw chuck (8")
- 4-jaw chucks (8")
- Steady rest (3.750")
- Thread chasing dial
- Spindle taper sleeve
- Full length splash guard

<b>Spindle bore :</b>	1.562"
<b>Attachment :</b>	D1 - 4
<b>Speed of the spindle :</b>	90 to 1800 rpm (8)
<b>Feeds :</b>	0.0012" – 0.0294" / revolution (40, longitudinal) 0.0004" – 0.0103" / revolution (40, transversal)
<b>Threads :</b>	Imperial : 4 to 112 tpi (40) Metric : 0.45 to 7.5 mm (22)
<b>Tailstock taper :</b>	MT #3
<b>Bed width :</b>	8 1/8"
<b>Tailstock travel :</b>	4.750"
<b>Motor :</b>	3 HP, 220V, 1ph,
<b>Dimensions :</b>	76" x 30" x 48" h
<b>Approximate weight :</b>	1 ,765lbs

\*Specifications and price are subject to changes without prior notice.  
\*Machines may differ from photo.



50 rue Delisle  
Lévis, Québec G6V 6K2  
Tél : (418) 837-5832  
Télé : (418) 837-6628  
Courriel : [info@garantmachinerie.com](mailto:info@garantmachinerie.com)

