



Geared head, engine lathe Model WSL1440HD

FOB Lévis*
Digital Readout Optional*

CAPACITIES :

Over ways : 14"
Over cross slide : 8.250"
Between centers : 40"
In gap : 20"

CHARACTERISTICS

- Clutch located on carriage
- Longitudinal & cross feeds
- Hardened & ground spindles
- Imperial & metric threading
- Hardened & ground bedways
- Simplified quick change levers
- High density cast iron base


INCLUDES

- Live center
- Follow rest
- Halogen lamp
- Quick toolpost
- Face plate (12")
- Removable gap
- Coolant system
- Tools & manual
- Production stop
- 3-jaw chuck (8")
- 4-jaw chuck (8")
- Steady rest (3.750")
- Thread chasing dial
- Spindle taper sleeve
- Full length splash guard

Spindle bore :	1.562"
Attachment :	D1 - 4
Speed of the spindle :	40 to 1800 rpm (12)
Feeds :	0.0012" – 0.0294" / revolution (40, longitudinal) 0.0004" – 0.0103" / revolution (40, transversal)
Threads :	Imperial : 4 to 112 tpi (40) Metric : 0.45 to 7.5 mm (22)
Tailstock taper :	MT #3
Bed width :	10.250"
Tailstock travel :	4.750"
Motor :	3 HP, 220V, 1ph, 60hz
Dimensions :	76" x 30" x 48"
Approximate weight :	2, 191 lbs

*Specifications and price are subject to changes without prior notice.

*Machines may differ from photo.



50 rue Delisle
Lévis, Québec G6V 6K2
Tél : (418) 837-5832
Télé : (418) 837-6628
Courriel : info@garantmachinerie.com

