



Toolroom lathe, variable speed Model WSL712V

FOB Lévis*

CAPACITIES :

Over ways : 7"
Over cross slide : 4 3/4"
Between centers : 12"

CHARACTERISTICS

- Emergency stop
- Gates driving belt
- Variable speed drive
- Forward/reverse switch
- Hardened & ground ways
- Spindle on precision bearings

INCLUDES

- Drill chuck
- Live center
- Facing plate
- Dead centers
- 4-way toolpost
- 3 & 4 jaw chucks
- Steady & follow rest
- Digital reading of spindle speed

Spindle bore :	0.8"
Speed of the spindle :	50 to 2500 rpm (infinitely variable)
Feeds :	0.002" – 0.012" mm / revolution (longitudinal)
Threads :	Imperial : 10 to 44 tpi Metric : 0.5 to 3 mm
Tailstock taper :	MT #2
Bed width :	4"
Tailstock travel :	2 1/4"
Crossslide travel :	3"
Motor :	0.6 HP, 110V, 1ph, 60hz
Dimensions :	32" x 19" x 18" h
Approximate weight :	132 lbs

*Specifications and price are subject to changes without prior notice.

*Machines may differ from photo.



50 rue Delisle
Lévis, Québec G6V 6K2
Tél : (418) 837-5832
Télé : (418) 837-6628
Courriel : info@garantmachinerie.com

