



Lathe / Mill combination

Model WSLM1126V

FOB Lévis*

CHARACTERISTICS

- Emergency stop
- Gates driving belt
- Forward/reverse switch
- T-slotted crossslide table
- Hardened & ground ways
- KB variable speed drive
- Spindle mounted on precision bearings

Accessories - Lathe

- Face plate
- Variable speed
- 4-way toolpost
- Fabricated stand
- 3 & 4 jaw chucks
- Digital reading of spindle speed

Accessories - Mill

- Collet set
- Drill chuck
- Clamping kit
- Variable speed
- Swivel milling vice
- Swivel head + / - 45 degrees
- Digital reading of spindle stroke

CAPACITIES MILL :

Over ways :	11"
Over carriage :	6 ⁵ / ₈ "
Between centers :	26"
Spindle bore :	1"
Spindle speeds :	50 to 2000 rpm (infinitely variable)
Cross feeds :	0.0008" – 0.011" / revolution
Longitudinal feeds :	0.002" – 0.012" / revolution
Threads :	Imperial : 8 to 56 tpi Metric : 0.4 to 3.5 mm
Tailstock taper :	MT #2
Bed width :	7"
Tailstock travel :	3 ¹ / ₈ "
Crossslide travel :	5 ¹ / ₂ "
Motor :	1 ¹ / ₃ HP, 110V, 1ph, 60hz
Dimensions :	54" x 27" x 50" h (with support)
Approximate weight :	

CAPACITIES Drill :

Drill :	³ / ₄ "
Mill :	³ / ₄ "
Surfacing :	2" (fly cutter)
Spindle :	stroke : 2" (with digital readout) taper : MT#2 speeds : 50 –2250 rpm
Distance spindle/ column :	6 ¹ / ₂ "
Distance spindle / table (max.) :	12"
Head travel (vertical) :	10"
Head inclination :	+ / - 45 degrees
Motor :	⁷ / ₈ HP , 110V, 1ph, 60hz

*Specifications and price are subject to changes without prior notice.

*Machines may differ from photo.



50 rue Delisle
Lévis, Québec G6V 6K2
Tél : (418) 837-5832
Télé : (418) 837-6628
Courriel : info@garantmachinerie.com

