

Power (tons)	50
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	800
Side opening useable (mm)	136
Vertical opening useable (mm)	200/1000
Side opening useable (mm)	163
Engine power (HP)	4
Pressing speed (mm/s)	420
Height (mm.)	2230
Width (mm.)	1170
Depth (mm.)	1000
Weight (Kg.)	480



Pressure regulator	•
Two-speed hydraulic unit	-
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	-
Special front opening 1500mm.	-
Folding equipment 415 mm	-
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent





Features

Power (tons)	80
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1000
Side opening useable (mm)	220
Vertical opening useable (mm)	260/860
Side opening useable (mm)	260
Engine power (HP)	4
Pressing speed (mm/s)	300
Height (mm.)	2340
Width (mm.)	1400
Depth (mm.)	1000
Weight (Kg.)	850

Accessories

Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	-
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent



* MACHINE EQUIPPED WITH OPTIONAL ACCESSORIES



Power (tons)	100
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1000
Side opening useable (mm)	240
Vertical opening useable (mm)	250/850
Side opening useable (mm)	280
Engine power (HP)	4
Pressing speed (mm/s)	240
Height (mm.)	2340
Width (mm.)	1400
Depth (mm.)	1000
Weight (Kg.)	1000



Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	-
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent





Power (tons)	125
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1000
Side opening useable (mm)	260
Vertical opening useable (mm)	240/840
Side opening useable (mm)	305
Engine power (HP)	4
Pressing speed (mm/s)	190
Height (mm.)	2340
Width (mm.)	1400
Depth (mm.)	1000
Weight (Kg.)	1150



Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	-
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent





Power (tons)	150
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1100
Side opening useable (mm)	280
Vertical opening useable (mm)	260/860
Side opening useable (mm)	330
Engine power (HP)	5,5
Pressing speed (mm/s)	230
Height (mm.)	2480
Width (mm.)	1570
Depth (mm.)	1200
Weight (Kg.)	1500



Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	•
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent



* MACHINE EQUIPPED WITH OPTIONAL ACCESSORIES



Power (tons)	200
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1100
Side opening useable (mm)	320
Vertical opening useable (mm)	250/850
Side opening useable (mm)	380
Engine power (HP)	5,5
Pressing speed (mm/s)	180
Height (mm.)	2480
Width (mm.)	1570
Depth (mm.)	1200
Weight (Kg.)	1960



Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	•
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent



* MACHINE EQUIPPED WITH OPTIONAL ACCESSORIES



Features

Power (tons)	250
Hydraulic system speeds.	1
Stroke (mm)	250
Front opening useable (mm)	1100
Side opening useable (mm)	350
Vertical opening useable (mm)	300/900
Side opening useable (mm)	420
Engine power (HP)	7,5
Pressing speed (mm/s)	145
Height (mm.)	2750
Width (mm.)	1610
Depth (mm.)	1200
Weight (Kg.)	2850

Accessories

Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	•
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	•
Special front opening 1500mm.	•
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent



* MACHINE EQUIPPED WITH OPTIONAL ACCESSORIES



Power (tons)	300
Hydraulic system speeds.	1
Stroke (mm)	300
Front opening useable (mm)	1500
Side opening useable (mm)	400
Vertical opening useable (mm)	300/1020
Side opening useable (mm)	500
Engine power (HP)	10
Pressing speed (mm/s)	150
Height (mm.)	3000
Width (mm.)	2050
Depth (mm.)	1300
Weight (Kg.)	4050



Pressure regulator	•
Two-speed hydraulic unit	•
Maneuver by means of electric pedals	S
Maneuver by means of two-hand controls	•
Limit switches and anti-spinning system	•
Motorised bedplate	S
Special front opening 1500mm.	S
Folding equipment 415 mm	•
Fixed rear guard	•
Safety front doors	•

^[•] Optional [S] Included [-] Nonexistent



* MACHINE EQUIPPED WITH OPTIONAL ACCESSORIES